





Part No:
DXR6UKSJ-WH
DXR6UKSJ-BL

DEXTEAR



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS
2. CURRENT RATING : 1.5 AMP
3. CONTACT RESISTANCE :100 MILLIOHMS MAX
4. INSULATION RESISTANCE :1000 MEGOHMS MIN @ 500 VDC
5. DIELECTRIC STRENGTH :750 VAC RMS 60Hz,1MIN
6. C6 PERMANENT LINK :CONFORM TO ANSI/TIA/EIA-568 B.1-2

ENVIRONMENTAL:

1. STORAGE : -40 TO +70°
 2. OPERATION: -10° TO +60°
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

MECHANICAL:

1. HOUSING MATERIAL :PC PA
2. INSERT MATERIAL :ABS
3. PCB MATERIAL :FR-4 T-1.0mm
4. CONTACT MATERIAL :PHOSPHOR BRONZE STAMP PIN T=0.35mm
5. IDC CONTACT MATERIAL :PHOSPHOR BRONZE T=0.50mm WITH TIN PLATING
6. RJ45 JACK LIFE :750 TIMES MIN
7. IDC LIFE :200 TIMES MIN
8. WIRE :AWG 24~22
9. TIA Cat 6 Perm. Link Test: Worst pair NEXT margin > 5.0dB 10 Petentiveness of insertion structure 50N 6015s

